

THIS IS TO SIGNIFY THAT THE FOLLOWING PRODUCTS FOR RESIDENTIAL CONSTRUCTION

KOPPERS HI-BOR/ADVANCE GUARD WOOD PRESERVATIVE TECHNOLOGY

MANUFACTURED BY

KOPPERS PERFORMANCE CHEMICALS

HAVE BEEN CERTIFIED FOR POINTS TOWARD NGBS GREEN CERTIFICATION TO THE ICC 700 NATIONAL GREEN BUILDING STANDARD AS DETAILED IN NGBS GREEN CERTIFIED PRODUCT REPORT #NGBSGCP-000153.

Thomas M. Kenney, P.E. – VP Research & Engineering

October 13, 2010
Approval Date

Expiration Date

July 31, 2021

CERTIFICATE #000153

This certificate is not a representation, warranty, or guarantee of product performance or certification of code compliance. For details of the product warranty, consult the product manufacturer.



NGBS Green Certified Product Report #NGBSGCP-000153

Products: Koppers Hi-bor/Advance Guard Wood Preservative Technology

Manufacturer: Koppers Performance Chemicals

The product(s) shown on this report have been independently verified as eligible products for use in achieving points toward project certification under ICC-700 National Green Building Standard. Home Innovation Research Labs authorizes accredited verifiers to award points toward certification without additional documentation when the product(s) is used as noted below.

2012 NATIONAL GREEN BUILDING STANDARD				
PRACTICE #	Practice Description	POTENTIAL POINTS AVAILABLE	Additional Conditions of Use to Award Points	
2012 NGBS 602.1.6	Termite-resistant materials are used in portions of the building.	2-6	To earn 2 points, product is used in conjunction with other termite resistant materials for the first 2' of all the foundation, floor, and structural wall, wall clading, and exterior deck components in zones with slight to moderate termite infestation. 4 points are awarded when used in the first 3' in moderate to heavy termite zones, and 6 points are awarded for use in all of the foundation, floor, and structural wall, wall clading, and exterior deck components in areas of very heavy termites.	
2012 NGBS 901.4(2-6)	A minimum of 85% of material within a product group (i.e., wood structural panels, countertops, composite trim/doors, custom woodwork, and/or component closet shelving) is manufactured in accordance with the following. 10 points maximum awarded.	2-4	A minimum of 85% of the product group in the building must be product that is compliant with this practice. Complaint products that are treated with Hibor/Advacned Guard Wood Preservative Technology remain complaint after treatment.	

2015 NATIONAL GREEN BUILDING STANDARD					
PRACTICE #	Practice Description	POTENTIAL POINTS AVAILABLE	Additional Conditions of Use to Award Points		
2015 NGBS 602.1.6	Termite-resistant materials are used in portions of the building.	2-6	To earn two points, product is used in conjunction with other termite resistant materials for the first 2 feet of all the foundation, floor, and structural wall, wall clading, and exterior deck components in zones with slight to moderate termite infestation. 4 points		

NGBS Green Certified Product Report #NGBSGCP-000153 Page 2 of 2

			are awarded when used in the first 3 feet in moderate to heavy termite zones, and 6 points are awarded for use in all of the foundation, floor, and structural wall, wall clading, and exterior deck components in areas of very heavy termites.
2015 NGBS 901.4(2-6)	A minimum of 85% of material within a product group (i.e., wood structural panels, countertops, composite trim/doors, custom woodwork, and/or component closet shelving) is manufactured in accordance with the following. 10 points maximum awarded.	2-4	A minimum of 85% of the product group in the building must be product that is compliant with this practice. Compliant products that are treated with Hibor/Advacned Guard Wood Preservative Technology remain complaint after treatment.

2020 NATIONAL GREEN BUILDING STANDARD				
PRACTICE #	PRACTICE DESCRIPTION	POTENTIAL POINTS AVAILABLE	Additional Conditions of Use to Award Points	
2020 NGBS 602.1.6	Termite-resistant materials are used in portions of the building.	2-6	To earn two points, product is used in conjunction with other termite resistant materials for the first 2 feet of all the foundation, floor, and structural wall, wall clading, and exterior deck components in zones with slight to moderate termite infestation. 4 points are awarded when used in the first 3 feet in moderate to heavy termite zones, and 6 points are awarded for use in all of the foundation, floor, and structural wall, wall clading, and exterior deck components in areas of very heavy termites.	
2020 NGBS 901.4(2-6)	A minimum of 85% of material within a product group (i.e., wood structural panels, countertops, composite trim/doors, custom woodwork, and/or component closet shelving) is manufactured in accordance with the following. 10 points maximum awarded.	2-4	A minimum of 85% of the product group in the building must be product that is compliant with this practice. Complaint products that are treated with Hibor/Advacned Guard Wood Preservative Technology remain complaint after treatment.	